



PERFORMANCE DATA SHEET  
NEMA PREMIUM NR CAN NEMA 12 - 12



Catalogue #: **MQOP-82**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
125	93.25	460	1.15	95.4%	0.87	405T	B	907

60 Hz								
FLA							Code	F.L. RPM
208	230	416	460	480	575	600		
/	/	155.9	141	135.1	/	/	G	1785

50 Hz								
FLA			S.F. @ 50Hz	Efficiency	Power Factor	Code	F.L. RPM	
190	380	415						
/	170	155.7	1.00	94.2%	0.88	D	1485	

Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
1342	3	Cont.	F	40°C	1000M (3300 Ft)	< 80

% Efficiency		% Power Factor		Torque		Winding Resist. Ω	Safe Cold Start (Secs)
Full Load:	95.4%	Full Load:	0.87	Full Load Ft/Lbs	368.9		
3/4 Load:	95.0%	3/4 Load:	0.86	Locked Rotor %	150	0	20
1/2 Load:	94.5%	1/2 Load:	0.81	Break Down %	250		

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
40.34	675	Standard	Cast Iron	Standard	Standard	ODP	IP23	5AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
6318	6314	Mobil PolyrexEm	Rigid	Horizontal	Green	88	100

Inverter Duty. Motor meets MG1 parts 31.4.4.2	Constant Torque Range	Variable Torque Range	Constant HP RPM
	10:1	20:1	2700

WIRING CONNECTION DIAGRAM : **B**

