



PERFORMANCE DATA SHEET

NEMA PREMIUM NR CAN NEMA 12 - 12



Catalogue #: **MQOP-98**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
200	149.20	460	1.15	95.4%	0.85	449T	B	1450

60 Hz								
FLA							Code	F.L. RPM
208	230	416	460	480	575	600		
/	/	254.3	230	220.4	/	/	G	1190

50 Hz								
FLA			S.F. @ 50Hz		Efficiency	Power Factor	Code	F.L. RPM
190	380	415						
/	290	265.5	1.00		94.3%	0.83	E	985

Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
2100	3	Cont.	F	40°C	1000M (3300 Ft)	< 80

% Efficiency		% Power Factor		Torque		Winding Resist. Ω	Safe Cold Start (Secs)
Full Load:	95.4%	Full Load:	0.85	Full Load Ft/Lbs	885.0		
3/4 Load:	95.0%	3/4 Load:	0.82	Locked Rotor %	150		
1/2 Load:	94.5%	1/2 Load:	0.75	Break Down %	245		
						0	20

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
142.38	2900	Standard	Cast Iron	Standard	Standard	ODP	IP23	3AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
NU318	6318						
		Mobil PolyrexEm	Rigid	Horizontal	Green	88	100

Inverter Duty. Motor meets MG1 parts 31.4.4.2	Constant Torque Range	Variable Torque Range	Constant HP RPM
	10:1	20:1	1800

WIRING CONNECTION DIAGRAM : C	
444T - 449T, Single Voltage, 6 Leads Connection 460 VAC 3 phase WYE Start DELTA Run	