



PERFORMANCE DATA SHEET
NEMA PREMIUM NR CAN NEMA 12 - 12



Catalogue #: **MQP-13**

HP	kW	Voltage	S.F. @ 60Hz	EFF.	P.F.	Frame	Design	L.R. Amps
2	1.49	230/460	1.25	88.5%	0.7	184T	B	25

60 Hz								
FLA							Code	F.L. RPM
208	230	416	460	480	575	600		
6.4	5.9	3.2	2.95	2.85	/	/	L	1180

50 Hz								
FLA			S.F. @ 50Hz	Efficiency	Power Factor	Code	F.L. RPM	
190	380	415						
7.0	3.5	3.2	1.00	86,5%	0.75	J	975	

Wgt. Lbs	PH	Duty	Insul. Class	Amb.	Elevation	Temp. Rise° C
103	3	Cont.	F	40°C	1000M (3300 Ft)	< 80

% Efficiency		% Power Factor		Torque		Winding Resist. Ω	Safe Cold Start (Secs)
Full Load:	88.5%	Full Load:	0.70	Full Load Ft/Lbs	9.1		
3/4 Load:	88.0%	3/4 Load:	0.69	Locked Rotor %	230	0	20
1/2 Load:	86.4%	1/2 Load:	0.56	Break Down %	300		

Rotor Inertia Wk2 Lb-Ft2	Max Load Inertia Wk2 Lb-Ft2	Shaft Material	Frame Material	DE Bracket Type	ODE Bracket Type	Enclosure	NEMA Rating	Lead Wire Size
0.33	44.1	Standard	Cast Iron	Standard	Standard	TEFC	IP55	16AWG

Ball Bearings		Grease	Mount Type	Orientation	Paint	Sound Pressure @ 3FT	Sound Power
DE	ODE						
6306	6306	Sealed Bearings	Rigid	Horizontal	Green	57	67

Inverter Duty. Motor meets MG1 parts 31.4.4.2	Constant Torque Range	Variable Torque Range	Constant HP RPM
	10:1	20:1	1800

WIRING CONNECTION DIAGRAM : **A**

143T - 184T, Dual Voltage, DOL, 9 Leads WYE Connection
230 / 460 VAC

